

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

## Performance

- ACEA: C5
- ILSAC: GF-6A
- Ford WSS-M2C947-B1
- GM DexosD™
- MB: 229.71
- OPEL/VAUXHALL: OV0401547
- Chrysler MS-12145
- API: SP RESOURCE CONSERVING
- BMW: LL-17 FE+
- Ford WSS-M2C962-A1
- Jaguar Land Rover STJLR.03.5006
- MB: 229.72
- VOLVO: VCC RBS0-2AE
- Fiat 9.55535-GSX

## Applications

A modern fuel economy, special composed synthetic motor oil suitable for use in petrol and diesel engines of passenger cars and delivery vans.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.845
Viscosity -35 °C	mPas	5260
Viscosity 40 °C	mm <sub>2</sub> /s	
Viscosity 100 °C	mm <sub>2</sub> /s	
Viscosity index		
Flash point COC	°C	
Pour point	°C	
Total Base Number	mgKOH/g	
Sulphated Ash	%	