

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

## Performance

- API: SN / RC / SN+                      • CHRYSLER: MS6395
- FORD: WSS-M2C945-A /  
WSS-M2C947-A /  
WSS-M2C946-A                      • GM: DEXOS 1 GEN 2
- ILSAC: GF-5

## Applications

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1 ? Gen 2

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.852
Viscosity -30 °C	mPas	3940
Viscosity 40 °C	mm <sub>2</sub> /s	48.00
Viscosity 100 °C	mm <sub>2</sub> /s	8.80
Flash point COC	°C	226
Pour point	°C	-33
Total Base Number	mgKOH/g	8.5
Sulphated Ash	%	0.89