

A synthetic automatic transmission fluid, based on synthetic base oils, formulated with special friction modifiers to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- an excellent stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties and consequently low noise and smooth switching
- compatible with synthetic seals
- a quick oil provision at cold start conditions

### Performance

- AUDI: TL 52180
- DODGE: NS-2/CVTF+4
- FORD: CVT30
- GM: SATURN DEX-CVT
- HONDA: HMMF
- HYUNDAI: SP-III
- KIA: SP-CVT 1
- MB: 236.20
- BMW: 83220136376 / 83220429159
- NISSAN: NS-1
- NISSAN: NS-3
- SUBARU: Lineartronic CVTF
- TOYOTA: TC
- VW: G 052 516
- Daihatsu Ammix CVT
- FORD: CVT23
- FORD: MERCON C
- HONDA: HCF-2
- HYUNDAI: SP-CVT1
- JEEP: NS-2/CVTF+4
- KIA: SP-III
- MINI: EZL799A
- MITSUBISHI: CVTF-J1/SP-III
- NISSAN: NS-2
- PUNCH: EZL799A
- SUZUKI: TC/NS-2/CVT Green 1
- VW: G 052 180

### Applications

This fluid may be used for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications. It is recommended to follow the instructions of the manufacturer.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.846
Viscosity 40 °C	mm <sub>2</sub> /s	36.60
Viscosity 100 °C	mm <sub>2</sub> /s	7.20
Viscosity index		165
Flash point COC	°C	212

Pour point	°C	-48
Total Base Number	mgKOH/g	2.7