

This is an oil with a high viscosity index for automatic transmissions. It is characterized by a high chemical stability, increased anti-wear properties and an excellent resistance against ageing.

## Performance

- ALLISON : C4
- FORD: M2C-138CJ, Mercon
- MAN: 339 V1/Z1
- MB: 236.7
- VOITH: H55.6335xx
- ZF: TE-ML 04D
- ZF: TE-ML 11A
- ZF: TE-ML 17C
- CATERPILLAR: TO-2
- GM: 6137-M DEXRON II-D
- MB: 236.5
- MB: 236.1
- ZF: TE-ML 03D
- ZF: TE-ML 09
- ZF: TE-ML 14A



## Features

Anti-wear protection : extended transmission life.  
Extended oil life : optimized thermal and oxidation stability.

## Applications

It can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron II-D requirements.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.867
Viscosity 40 °C	mm <sup>2</sup> /s	37.40
Viscosity 100 °C	mm <sup>2</sup> /s	7.46
Viscosity index		171
Flash point COC	°C	198
Pour point	°C	-48
Total Base Number	mgKOH/g	2.4