

A very high graded, extremely low-viscosity automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- excellent contribution to fuel economy
- excellent lubrication
- very good resistance against oxidation
- very good thermal stability
- excellent and very stable friction characteristics
- excellent resistance against corrosion and foaming
- excellent protection against wear
- a very high and stable viscosity index

Performance

- MB 236.17

Applications

This premium synthetic product is specially formulated for the lubrication of certain Mercedes-Benz automatic transmissions with 9 gears. This oil contributes significantly to realizing fuel saving and can be used in automatic transmissions where an oil with the specification MB 236.17 is prescribed.

ATF MB 17 must not be used in older generations of the Mercedes Benz 5 and 7-gear automatic transmissions. Here an automatic transmission oil according to MB standard MB-Norm 236.10, 236.12, 236.14 or 236.15 is specified. For more informations and specifications, please contact our sales team or visit our website.

Characteristics	Unit	Average
Density at 15 °C	kg/l	0.835
Viscosity 40 °C	mm ₂ /s	17.10
Viscosity 100 °C	mm ₂ /s	4.23
Viscosity index		161
Flash point COC	°C	190
Pour point	°C	-54